



臺灣宇頂

模具彈簧

YU-DIING DIE SPRING

プレス型用コイルばね
JIS B5012



宇頂企業股份有限公司

Yu-Diing Enterprise Co.,LTD.

TEL: +886-2-86885959

宇頂模具彈簧系列目錄

Catalog of Yu-Diing Die Spring Series

Made in Taiwan



YF輕小荷重

YF Series Die Springs : Lightest Load

規格標準: 符合JIS B 5012

Standard Reference: JIS B 5012

材質/截面: 彈簧合金鋼/矩形截面

Material /Shape: Rectangular spring alloy wire

表面: 烤漆黃色

Surface: baking paint,yellow color



YL輕荷重

YL Series Die Springs : Light Load

規格標準: 符合JIS B 5012

Standard Reference: JIS B 5012

材質/截面: 彈簧合金鋼/矩形截面

Material /Shape: Rectangular spring alloy wire

表面: 烤漆藍色

Surface: baking paint,blue color



YM中荷重

YM Series Die Springs : Medium Load

規格標準: 符合JIS B 5012

Standard Reference: JIS B 5012

材質/截面: 彈簧合金鋼/矩形截面

Material /Shape: Rectangular spring alloy wire

表面: 烤漆紅色

Surface: baking paint,red color



YH重荷重

YH Series Die Springs : Heavy Load

規格標準: 符合JIS B 5012

Standard Reference: JIS B 5012

材質/截面: 彈簧合金鋼/矩形截面

Material /Shape: Rectangular spring alloy wire

表面: 烤漆綠色

Surface: baking paint,green color



YB極重荷重

YB Series Die Springs : Super Load

規格標準: 符合JIS B 5012

Standard Reference: JIS B 5012

材質/截面: 彈簧合金鋼/矩形截面

Material /Shape: Rectangular spring alloy wire

表面: 烤漆茶色

Surface: baking paint,brown color



LR圓線彈簧

LR Series Springs : Round Coil Spring

規格標準: 符合JIS B 5012

Standard Reference: JIS B 5012

材質/截面: 彈簧合金鋼/圓形截面

Material/section: spring alloy steel/round section

表面: 塗防銹油

Surface: Apply anti-rust oil

YF 輕小荷重

LIGHTEST LOAD

台灣製造
MADE IN TAIWAN

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YF08x10	8	4	2.00	5.0	10	4.5	9	4.0	8	10
15			1.33	7.5		6.8		6.0		15
20			1.00	10.0		9.0		8.0		20
25			0.80	12.5		11.3		10.0		25
30			0.67	15.0		13.5		12.0		30
35			0.57	17.5		15.8		14.0		35
40			0.50	20.0		18.0		16.0		40
45			0.44	22.5		20.3		18.0		45
50			0.40	25.0		22.5		20.0		50
55			0.36	27.5		24.8		22.0		55
60			0.33	30.0		27.0		24.0		60
65			0.31	32.5		29.3		26.0		65
70			0.29	35.0		31.5		28.0		70
75			0.27	37.5		33.8		30.0		75
80			0.25	40.0		36.0		32.0		80
90			0.22	45.0		40.5		36.0		90
100			0.20	50.0		45.0		40.0		100
YF10x10	10	5	3.60	5.0	18	4.5	16	4.0	14	10
15			2.40	7.5		6.8		6.0		15
20			1.80	10.0		9.0		8.0		20
25			1.44	12.5		11.3		10.0		25
30			1.20	15.0		13.5		12.0		30
35			1.03	17.5		15.8		14.0		35
40			0.90	20.0		18.0		16.0		40
45			0.80	22.5		20.3		18.0		45
50			0.72	25.0		22.5		20.0		50
55			0.65	27.5		24.8		22.0		55
60			0.60	30.0		27.0		24.0		60
65			0.55	32.5		29.3		26.0		65
70			0.51	35.0		31.5		28.0		70
75			0.48	37.5		33.8		30.0		75
80			0.45	40.0		36.0		32.0		80
90			0.40	45.0		40.5		36.0		90
100			0.36	50.0		45.0		40.0		100
YF12x15	12	6	2.93	7.5	22	6.8	20	6.0	18	15
20			2.20	10.0		9.0		8.0		20
25			1.76	12.5		11.3		10.0		25
30			1.47	15.0		13.5		12.0		30
35			1.26	17.5		15.8		14.0		35
40			1.10	20.0		18.0		16.0		40
45			0.98	22.5		20.3		18.0		45
50			0.88	25.0		22.5		20.0		50
55			0.80	27.5		24.8		22.0		55
60			0.73	30.0		27.0		24.0		60
65			0.68	32.5		29.3		26.0		65
70			0.63	35.0		31.5		28.0		70
75			0.59	37.5		33.8		30.0		75
80			0.55	40.0		36.0		32.0		80
90			0.49	45.0		40.5		36.0		90
100			0.44	50.0		45.0		40.0		100

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YF25x50=50pcs

交貨日期：現貨供應。

YF 輕小荷重

LIGHTEST LOAD

台灣製造
MADE IN TAIWAN

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YF14x20	14	7	2.10	10.0	21	9.0	19	8.0	17	20
25			1.68	12.5		11.3		10.0		25
30			1.40	15.0		13.5		12.0		30
35			1.20	17.5		15.8		14.0		35
40			1.05	20.0		18.0		16.0		40
45			0.93	22.5		20.3		18.0		45
50			0.84	25.0		22.5		20.0		50
55			0.76	27.5		24.8		22.0		55
60			0.70	30.0		27.0		24.0		60
65			0.65	32.5		29.3		26.0		65
70			0.60	35.0		31.5		28.0		70
75			0.56	37.5		33.8		30.0		75
80			0.53	40.0		36.0		32.0		80
85			0.49	42.5		38.3		34.0		85
90			0.47	45.0		40.5		36.0		90
100			0.42	50.0		45.0		40.0		100
125			0.34	62.5		56.3		50.0		125
YF16x20	16	8	2.30	10.0	23	9.0	21	8.0	18	20
25			1.84	12.5		11.3		10.0		25
30			1.53	15.0		13.5		12.0		30
35			1.31	17.5		15.8		14.0		35
40			1.15	20.0		18.0		16.0		40
45			1.02	22.5		20.3		18.0		45
50			0.92	25.0		22.5		20.0		50
55			0.84	27.5		24.8		22.0		55
60			0.77	30.0		27.0		24.0		60
65			0.71	32.5		29.3		26.0		65
70			0.66	35.0		31.5		28.0		70
75			0.61	37.5		33.8		30.0		75
80			0.58	40.0		36.0		32.0		80
85			0.54	42.5		38.3		34.0		85
90			0.51	45.0		40.5		36.0		90
100			0.46	50.0		45.0		40.0		100
125			0.37	62.5		56.3		50.0		125
YF18x25	18	9	2.08	12.5	26	11.3	23	10.0	21	25
30			1.73	15.0		13.5		12.0		30
35			1.49	17.5		15.8		14.0		35
40			1.30	20.0		18.0		16.0		40
45			1.16	22.5		20.3		18.0		45
50			1.04	25.0		22.5		20.0		50
55			0.95	27.5		24.8		22.0		55
60			0.87	30.0		27.0		24.0		60
65			0.80	32.5		29.3		26.0		65
70			0.74	35.0		31.5		28.0		70
75			0.69	37.5		33.8		30.0		75
80			0.65	40.0		36.0		32.0		80
90			0.58	45.0		40.5		36.0		90
100			0.52	50.0		45.0		40.0		100
125			0.42	62.5		56.3		50.0		125
150			0.35	75.0		67.5		60.0		150
YF20x20			20	12		3.00		10.0		30
25	2.40	12.5			11.3	10.0	25			
30	2.00	15.0			13.5	12.0	30			
35	1.71	17.5			15.8	14.0	35			
40	1.50	20.0			18.0	16.0	40			
45	1.33	22.5			20.3	18.0	45			
50	1.20	25.0			22.5	20.0	50			
55	1.09	27.5			24.8	22.0	55			
60	1.00	30.0			27.0	24.0	60			
65	0.92	32.5			29.3	26.0	65			
70	0.86	35.0			31.5	28.0	70			
75	0.80	37.5			33.8	30.0	75			
80	0.75	40.0			36.0	32.0	80			
90	0.67	45.0			40.5	36.0	90			
100	0.60	50.0			45.0	40.0	100			
125	0.48	62.5			56.3	50.0	125			
150	0.40	75.0			67.5	60.0	150			

YF 輕小荷重

LIGHTEST LOAD

台灣製造
MADE IN TAIWAN

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YF22x25	22	11	3.20	12.5	40	11.3	36	10.0	32	25
30			2.67	15.0		13.5		12.0		30
35			2.29	17.5		15.8		14.0		35
40			2.00	20.0		18.0		16.0		40
45			1.78	22.5		20.3		18.0		45
50			1.60	25.0		22.5		20.0		50
55			1.45	27.5		24.8		22.0		55
60			1.33	30.0		27.0		24.0		60
65			1.23	32.5		29.3		26.0		65
70			1.14	35.0		31.5		28.0		70
75			1.07	37.5		33.8		30.0		75
80			1.00	40.0		36.0		32.0		80
90			0.89	45.0		40.5		36.0		90
100			0.80	50.0		45.0		40.0		100
125			0.64	62.5		56.3		50.0		125
150	0.53	75.0	67.5	60.0	150					
YF25x25	25	13.5	5.28	12.5	66	11.3	59	10.0	52	25
30			4.40	15.0		13.5		12.0		30
35			3.77	17.5		15.8		14.0		35
40			3.30	20.0		18.0		16.0		40
45			2.93	22.5		20.3		18.0		45
50			2.64	25.0		22.5		20.0		50
55			2.40	27.5		24.8		22.0		55
60			2.20	30.0		27.0		24.0		60
65			2.03	32.5		29.3		26.0		65
70			1.89	35.0		31.5		28.0		70
75			1.76	37.5		33.8		30.0		75
80			1.65	40.0		36.0		32.0		80
90			1.47	45.0		40.5		36.0		90
100			1.32	50.0		45.0		40.0		100
125			1.06	62.5		56.3		50.0		125
150	0.88	75.0	67.5	60.0	150					
175	0.75	87.5	78.8	70.0	175					
200	0.66	100	90	80	200					
YF30X25	30	16	7.28	12.5	91	11.3	82	10.0	73	25
30			6.07	15.0		13.5		12.0		30
35			5.20	17.5		15.8		14.0		35
40			4.55	20.0		18.0		16.0		40
45			4.04	22.5		20.3		18.0		45
50			3.64	25.0		22.5		20.0		50
55			3.31	27.5		24.8		22.0		55
60			3.03	30.0		27.0		24.0		60
65			2.80	32.5		29.3		26.0		65
70			2.60	35.0		31.5		28.0		70
75			2.43	37.5		33.8		30.0		75
80			2.28	40.0		36.0		32.0		80
90			2.02	45.0		40.5		36.0		90
100			1.82	50.0		45.0		40.0		100
125			1.46	62.5		56.3		50.0		125
150	1.21	75.0	67.5	60.0	150					
175	1.04	87.5	78.8	70.0	175					
200	0.91	100	90	80	200					

訂購方法：型號（顏色）-外徑 x 長度=數量
 訂購示範：YF25x50=50pcs
 交貨日期：現貨供應。

YF 輕小荷重

LIGHTEST LOAD

台灣製造
MADE IN TAIWAN

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YF35x40	35	21	6.5	20.0	130	18.0	117	16.0	104	40
45			5.8	22.5		20.3		18.0		45
50			5.2	25.0		22.5		20.0		50
55			4.7	27.5		24.8		22.0		55
60			4.3	30.0		27.0		24.0		60
65			4.0	32.5		29.3		26.0		65
70			3.7	35.0		31.5		28.0		70
75			3.5	37.5		33.8		30.0		75
80			3.3	40.0		36.0		32.0		80
90			2.9	45.0		40.5		36.0		90
100			2.6	50.0		45.0		40.0		100
125			2.1	62.5		56.3		50.0		125
150			1.7	75.0		67.5		60.0		150
175			1.5	87.5		78.8		70.0		175
200			1.3	100.0		90.0		80.0		200
YF40x40			40	25		7.90		20.0		158
45	7.02	22.5			20.3	18.0	45			
50	6.32	25.0			22.5	20.0	50			
55	5.75	27.5			24.8	22.0	55			
60	5.27	30.0			27.0	24.0	60			
65	4.86	32.5			29.3	26.0	65			
70	4.51	35.0			31.5	28.0	70			
75	4.21	37.5			33.8	30.0	75			
80	3.95	40.0			36.0	32.0	80			
90	3.51	45.0			40.5	36.0	90			
100	3.16	50.0			45.0	40.0	100			
125	2.53	62.5			56.3	50.0	125			
150	2.11	75.0			67.5	60.0	150			
175	1.81	87.5			78.8	70.0	175			
200	1.58	100.0			90.0	80.0	200			
225	1.40	112.5			101.3	90.0	225			
250	1.26	125.0	112.5	100.0	250					
275	1.15	137.5	123.8	110.0	275					
300	1.05	150.0	135.0	120.0	300					
YF50X50	50	30	7.60	25.0	190	22.5	171	20.0	152	50
55			6.90	27.5		24.8		22.0		55
60			6.33	30.0		27.0		24.0		60
65			5.85	32.5		29.3		26.0		65
70			5.43	35.0		31.5		28.0		70
75			5.07	37.5		33.8		30.0		75
80			4.75	40.0		36.0		32.0		80
90			4.22	45.0		40.5		36.0		90
100			3.80	50.0		45.0		40.0		100
125			3.04	62.5		56.3		50.0		125
150			2.53	75.0		67.5		60.0		150
175			2.17	87.5		78.8		70.0		175
200			1.90	100.0		90.0		80.0		200
225			1.69	112.5		101.3		90.0		225
250			1.52	125.0		112.5		100.0		250
275			1.38	137.5		123.8		110.0		275
300	1.27	150.0	135.0	120.0	300					
YF60X60	60	36	11.67	30.0	350	27.0	315	24.0	280	60
65			10.77	32.5		29.3		26.0		65
70			10.00	35.0		31.5		28.0		70
75			9.33	37.5		33.8		30.0		75
80			8.75	40.0		36.0		32.0		80
90			7.78	45.0		40.5		36.0		90
100			7.00	50.0		45.0		40.0		100
125			5.60	62.5		56.3		50.0		125
150			4.67	75.0		67.5		60.0		150
175			4.00	87.5		78.8		70.0		175
200			3.50	100.0		90.0		80.0		200
250			2.80	125.0		112.5		100.0		250
300	2.33	150.0	135.0	120.0	300					

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YL08x10	8	4	3.75	4.0	15	3.6	13	3.2	12	10
15			2.50	6.0		5.4		4.8		15
20			1.88	8.0		7.2		6.4		20
25			1.50	10.0		9.0		8.0		25
30			1.25	12.0		10.8		9.6		30
35			1.07	14.0		12.6		11.2		35
40			0.94	16.0		14.4		12.8		40
45			0.83	18.0		16.2		14.4		45
50			0.75	20.0		18.0		16.0		50
55			0.68	22.0		19.8		17.6		55
60			0.63	24.0		21.6		19.2		60
65			0.58	26.0		23.4		20.8		65
70			0.54	28.0		25.2		22.4		70
75			0.50	30.0		27.0		24.0		75
80			0.47	32.0		28.8		25.6		80
85			0.44	34.0		30.6		27.2		85
90			0.42	36.0		32.4		28.8		90
95			0.39	38.0		34.2		30.4		95
100			0.38	40.0		36.0		32.0		100
YL10x10			10	5.5		3.50		4.0		14
15	2.33	6.0			5.4	4.8	15			
20	1.75	8.0			7.2	6.4	20			
25	1.40	10.0			9.0	8.0	25			
30	1.17	12.0			10.8	9.6	30			
35	1.00	14.0			12.6	11.2	35			
40	0.88	16.0			14.4	12.8	40			
45	0.78	18.0			16.2	14.4	45			
50	0.70	20.0			18.0	16.0	50			
55	0.64	22.0			19.8	17.6	55			
60	0.58	24.0			21.6	19.2	60			
65	0.54	26.0			23.4	20.8	65			
70	0.50	28.0			25.2	22.4	70			
75	0.47	30.0			27.0	24.0	75			
80	0.44	32.0			28.8	25.6	80			
85	0.41	34.0			30.6	27.2	85			
90	0.39	36.0			32.4	28.8	90			
95	0.37	38.0			34.2	30.4	95			
100	0.35	40.0			36.0	32.0	100			
YL12x15	12	6.5			3.50	6.0	21	5.4	19	
20			2.63	8.0	7.2	6.4		20		
25			2.10	10.0	9.0	8.0		25		
30			1.75	12.0	10.8	9.6		30		
35			1.50	14.0	12.6	11.2		35		
40			1.31	16.0	14.4	12.8		40		
45			1.17	18.0	16.2	14.4		45		
50			1.05	20.0	18.0	16.0		50		
55			0.95	22.0	19.8	17.6		55		
60			0.88	24.0	21.6	19.2		60		
65			0.81	26.0	23.4	20.8		65		
70			0.75	28.0	25.2	22.4		70		
75			0.70	30.0	27.0	24.0		75		
80			0.66	32.0	28.8	25.6		80		
90			0.59	36.0	32.4	28.8		90		
100			0.53	40.0	36.0	32.0		100		

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YL25x50=50pcs

交貨日期：現貨供應。

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YL14x20	14	7	3.50	8.0	28	7.2	25	6.4	22	20
25			2.80	10.0		9.0		8.0		25
30			2.33	12.0		10.8		9.6		30
35			2.00	14.0		12.6		11.2		35
40			1.75	16.0		14.4		12.8		40
45			1.56	18.0		16.2		14.4		45
50			1.40	20.0		18.0		16.0		50
55			1.27	22.0		19.8		17.6		55
60			1.17	24.0		21.6		19.2		60
65			1.08	26.0		23.4		20.8		65
70			1.00	28.0		25.2		22.4		70
75			0.93	30.0		27.0		24.0		75
80			0.88	32.0		28.8		25.6		80
85			0.82	34.0		30.6		27.2		85
90			0.78	36.0		32.4		28.8		90
100	0.70	40	36.0	32.0	100					
125	0.56	50.0	45.0	40.0	125					
YL16x20	16	8	4.38	8.0	35	7.2	32	6.4	28	20
25			3.50	10.0		9.0		8.0		25
30			2.92	12.0		10.8		9.6		30
35			2.50	14.0		12.6		11.2		35
40			2.19	16.0		14.4		12.8		40
45			1.94	18.0		16.2		14.4		45
50			1.75	20.0		18.0		16.0		50
55			1.59	22.0		19.8		17.6		55
60			1.46	24.0		21.6		19.2		60
65			1.35	26.0		23.4		20.8		65
70			1.25	28.0		25.2		22.4		70
75			1.17	30.0		27.0		24.0		75
80			1.09	32.0		28.8		25.6		80
85			1.03	34.0		30.6		27.2		85
90			0.97	36.0		32.4		28.8		90
100	0.88	40.0	36.0	32.0	100					
125	0.70	50.0	45.0	40.0	125					
YL18x20	18	9	5.38	8.0	43	7.2	39	6.4	34	20
25			4.30	10.0		9.0		8.0		25
30			3.58	12.0		10.8		9.6		30
35			3.07	14.0		12.6		11.2		35
40			2.69	16.0		14.4		12.8		40
45			2.39	18.0		16.2		14.4		45
50			2.15	20.0		18.0		16.0		50
55			1.95	22.0		19.8		17.6		55
60			1.79	24.0		21.6		19.2		60
65			1.65	26.0		23.4		20.8		65
70			1.54	28.0		25.2		22.4		70
75			1.43	30.0		27.0		24.0		75
80			1.34	32.0		28.8		25.6		80
90			1.19	36.0		32.4		28.8		90
100			1.08	40.0		36.0		32.0		100
125	0.86	50.0	45.0	40.0	125					
YL20x20	20	12	6.88	8.0	55	7.2	50	6.4	44	20
25			5.50	10.0		9.0		8.0		25
30			4.58	12.0		10.8		9.6		30
35			3.93	14.0		12.6		11.2		35
40			3.44	16.0		14.4		12.8		40
45			3.06	18.0		16.2		14.4		45
50			2.75	20.0		18.0		16.0		50
55			2.50	22.0		19.8		17.6		55
60			2.29	24.0		21.6		19.2		60
65			2.12	26.0		23.4		20.8		65
70			1.96	28.0		25.2		22.4		70
75			1.83	30.0		27.0		24.0		75
80			1.72	32.0		28.8		25.6		80
90			1.53	36.0		32.4		28.8		90
100			1.38	40.0		36.0		32.0		100
125	1.10	50.0	45.0	40.0	125					
150	0.92	60.0	54.0	48.0	150					

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YL22x25	22	12	8.00	10.0	80	9.0	72	8.0	64	25
30			6.67	12.0		10.8		9.6		30
35			5.71	14.0		12.6		11.2		35
40			5.00	16.0		14.4		12.8		40
45			4.44	18.0		16.2		14.4		45
50			4.00	20.0		18.0		16.0		50
55			3.64	22.0		19.8		17.6		55
60			3.33	24.0		21.6		19.2		60
65			3.08	26.0		23.4		20.8		65
70			2.86	28.0		25.2		22.4		70
75			2.67	30.0		27.0		24.0		75
80			2.50	32.0		28.8		25.6		80
90			2.22	36.0		32.4		28.8		90
100			2.00	40.0		36.0		32.0		100
125			1.60	50.0		45.0		40.0		125
150	1.33	60.0	54.0	48.0	150					
YL25X25	25	13	9.90	10.0	99	9.0	89	8.0	79	25
30			8.25	12.0		10.8		9.6		30
35			7.07	14.0		12.6		11.2		35
40			6.19	16.0		14.4		12.8		40
45			5.50	18.0		16.2		14.4		45
50			4.95	20.0		18.0		16.0		50
55			4.50	22.0		19.8		17.6		55
60			4.13	24.0		21.6		19.2		60
65			3.81	26.0		23.4		20.8		65
70			3.54	28.0		25.2		22.4		70
75			3.30	30.0		27.0		24.0		75
80			3.09	32.0		28.8		25.6		80
90			2.75	36.0		32.4		28.8		90
100			2.48	40.0		36.0		32.0		100
125			1.98	50.0		45.0		40.0		125
150	1.65	60.0	54.0	48.0	150					
175	1.41	70.0	63.0	56.0	175					
200	1.24	80.0	72.0	64.0	200					
YL30x25	30	18	14.60	10.0	146	9.0	131	8.0	116	25
30			12.17	12.0		10.8		9.6		30
35			10.43	14.0		12.6		11.2		35
40			9.13	16.0		14.4		12.8		40
45			8.11	18.0		16.2		14.4		45
50			7.30	20.0		18.0		16.0		50
55			6.64	22.0		19.8		17.6		55
60			6.08	24.0		21.6		19.2		60
65			5.62	26.0		23.4		20.8		65
70			5.21	28.0		25.2		22.4		70
75			4.87	30.0		27.0		24.0		75
80			4.56	32.0		28.8		25.6		80
90			4.06	36.0		32.4		28.8		90
100			3.65	40.0		36.0		32.0		100
125			2.92	50.0		45.0		40.0		125
150	2.43	60.0	54.0	48.0	150					
175	2.09	70.0	63.0	56.0	175					
200	1.83	80.0	72.0	64.0	200					

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YL25x50=50pcs

交貨日期：現貨供應。

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YL35x40	35	21	10.94	16.0	175	14.4	157	12.8	140	40
45			9.72	18.0		16.2		14.4		45
50			8.75	20.0		18.0		16.0		50
55			7.95	22.0		19.8		17.6		55
60			7.29	24.0		21.6		19.2		60
65			6.73	26.0		23.4		20.8		65
70			6.25	28.0		25.2		22.4		70
75			5.83	30.0		27.0		24.0		75
80			5.47	32.0		28.8		25.6		80
90			4.86	36.0		32.4		28.8		90
100			4.38	40.0		36.0		32.0		100
125			3.50	50.0		45.0		40.0		125
150			2.92	60.0		54.0		48.0		150
175			2.50	70.0		63.0		56.0		175
200			2.19	80.0		72.0		64.0		200
YL40x40			40	26		13.13		16.0		210
45	11.67	18.0			16.2	14.4	45			
50	10.50	20.0			18.0	16.0	50			
55	9.55	22.0			19.8	17.6	55			
60	8.75	24.0			21.6	19.2	60			
65	8.08	26.0			23.4	20.8	65			
70	7.50	28.0			25.2	22.4	70			
75	7.00	30.0			27.0	24.0	75			
80	6.56	32.0			28.8	25.6	80			
90	5.83	36.0			32.4	28.8	90			
100	5.25	40.0			36.0	32.0	100			
125	4.20	50.0			45.0	40.0	125			
150	3.50	60.0			54.0	48.0	150			
175	3.00	70.0			63.0	56.0	175			
200	2.63	80.0			72.0	64.0	200			
225	2.33	90.0			81.0	72.0	225			
250	2.10	100.0	90.0	80.0	250					
275	1.90	110.0	99.0	88.0	275					
300	1.75	120.0	108.0	96.0	300					
YL50x50	50	32	16.50	20.0	330	18.0	297	16.0	264	50
55			15.00	22.0		19.8		17.6		55
60			13.75	24.0		21.6		19.2		60
65			12.69	26.0		23.4		20.8		65
70			11.79	28.0		25.2		22.4		70
75			11.00	30.0		27.0		24.0		75
80			10.31	32.0		28.8		25.6		80
90			9.17	36.0		32.4		28.8		90
100			8.25	40.0		36.0		32.0		100
125			6.60	50.0		45.0		40.0		125
150			5.50	60.0		54.0		48.0		150
175			4.71	70.0		63.0		56.0		175
200			4.13	80.0		72.0		64.0		200
250			3.30	100.0		90.0		80.0		250
300			2.75	120.0		108.0		96.0		300
YL60X60			60	33		23.96		24.0		575
70	20.54	28.0			25.2	22.4	70			
80	17.97	32.0			28.8	25.6	80			
90	15.97	36.0			32.4	28.8	90			
100	14.38	40.0			36.0	32.0	100			
125	11.50	50.0			45.0	40.0	125			
150	9.58	60.0			54.0	48.0	150			
175	8.21	70.0			63.0	56.0	175			
200	7.19	80.0			72.0	64.0	200			
250	5.75	100.0			90.0	80.0	250			
300	4.79	120.0			108.0	96.0	300			

YM 中荷重

台灣製造

MADE IN TAIWAN

MEDIUM LOAD

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30万 0.3million		50万 0.5million		100万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YM08x10	8	4	4.69	3.2	15	13	12	2.7	10	
15			3.13	4.8				3.8	15	
20			2.34	6.4				5.1	20	
25			1.88	8.0				6.4	25	
30			1.56	9.6				7.7	30	
35			1.34	11.2				9.0	35	
40			1.17	12.8				10.2	40	
45			1.04	14.4				11.5	45	
50			0.94	16.0				12.8	50	
55			0.85	17.6				14.1	55	
60			0.78	19.2				15.4	60	
65			0.72	20.8				16.6	65	
70			0.67	22.4				17.9	70	
75			0.63	24.0				19.2	75	
80			0.59	25.6				20.5	80	
85			0.55	27.2				21.8	85	
90			0.52	28.8				23.0	90	
95			0.49	30.4				24.3	95	
100			0.47	32.0				25.6	100	
YM10x10			10	5				6.25	3.2	20
15	4.17	4.8			3.8	15				
20	3.13	6.4			5.1	20				
25	2.50	8.0			6.4	25				
30	2.08	9.6			7.7	30				
35	1.79	11.2			9.0	35				
40	1.56	12.8			10.2	40				
45	1.39	14.4			11.5	45				
50	1.25	16.0			12.8	50				
55	1.14	17.6			14.1	55				
60	1.04	19.2			15.4	60				
65	0.96	20.8			16.6	65				
70	0.89	22.4			17.9	70				
75	0.83	24.0			19.2	75				
80	0.78	25.6			20.5	80				
85	0.73	27.2			21.8	85				
90	0.69	28.8			23.0	90				
95	0.66	30.4			24.3	95				
100	0.63	32.0			25.6	100				
YM12x15	12	6			6.04	4.8	29	26	23	
20			4.53	6.4	5.1	20				
25			3.63	8.0	6.4	25				
30			3.02	9.6	7.7	30				
35			2.59	11.2	9.0	35				
40			2.27	12.8	10.2	40				
45			2.01	14.4	11.5	45				
50			1.81	16.0	12.8	50				
55			1.65	17.6	14.1	55				
60			1.51	19.2	15.4	60				
65			1.39	20.8	16.6	65				
70			1.29	22.4	17.9	70				
75			1.21	24.0	19.2	75				
80			1.13	25.6	20.5	80				
85			1.07	27.2	21.8	85				
90			1.01	28.8	23.0	90				
95			0.95	30.4	24.3	95				
100			0.91	32.0	25.6	100				

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YM25x50=50pcs

交貨日期：現貨供應。

YM 中荷重

台灣製造

MADE IN TAIWAN

MEDIUM LOAD

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 萬 0.3million		50 萬 0.5million		100 萬 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YM14x20	14	7	6.09	6.4	39	5.8	35	5.1	31	20
25			4.88	8.0		7.2		6.4		25
30			4.06	9.6		8.6		7.7		30
35			3.48	11.2		10.1		9.0		35
40			3.05	12.8		11.5		10.2		40
45			2.71	14.4		13.0		11.5		45
50			2.44	16.0		14.4		12.8		50
55			2.22	17.6		15.8		14.1		55
60			2.03	19.2		17.3		15.4		60
65			1.88	20.8		18.7		16.6		65
70			1.74	22.4		20.2		17.9		70
75			1.63	24.0		21.6		19.2		75
80			1.52	25.6		23.0		20.5		80
90			1.35	28.8		25.9		23.0		90
100			1.22	32.0		28.8		25.6		100
125	0.98	40.0	36.0	32.0	125					
YM16x20	16	8	7.97	6.4	51	5.8	46	5.1	41	20
25			6.38	8.0		7.2		6.4		25
30			5.31	9.6		8.6		7.7		30
35			4.55	11.2		10.1		9.0		35
40			3.98	12.8		11.5		10.2		40
45			3.54	14.4		13.0		11.5		45
50			3.19	16.0		14.4		12.8		50
55			2.90	17.6		15.8		14.1		55
60			2.66	19.2		17.3		15.4		60
65			2.45	20.8		18.7		16.6		65
70			2.28	22.4		20.2		17.9		70
75			2.13	24.0		21.6		19.2		75
80			1.99	25.6		23.0		20.5		80
90			1.77	28.8		25.9		23.0		90
100			1.59	32.0		28.8		25.6		100
125	1.28	40.0	36.0	32.0	125					
YM18x20	18	9	10.16	6.4	65	5.8	58	5.1	52	20
25			8.13	8.0		7.2		6.4		25
30			6.77	9.6		8.6		7.7		30
35			5.80	11.2		10.1		9.0		35
40			5.08	12.8		11.5		10.2		40
45			4.51	14.4		13.0		11.5		45
50			4.06	16.0		14.4		12.8		50
55			3.69	17.6		15.8		14.1		55
60			3.39	19.2		17.3		15.4		60
65			3.13	20.8		18.7		16.6		65
70			2.90	22.4		20.2		17.9		70
75			2.71	24.0		21.6		19.2		75
80			2.54	25.6		23.0		20.5		80
90			2.26	28.8		25.9		23.0		90
100			2.03	32.0		28.8		25.6		100
125	1.63	40.0	36.0	32.0	125					
150	1.35	48.0	43.2	38.4	150					
YM20x20	20	10	12.50	6.4	80	5.8	72	5.1	64	20
25			10.00	8.0		7.2		6.4		25
30			8.33	9.6		8.6		7.7		30
35			7.14	11.2		10.1		9.0		35
40			6.25	12.8		11.5		10.2		40
45			5.56	14.4		13.0		11.5		45
50			5.00	16.0		14.4		12.8		50
55			4.55	17.6		15.8		14.1		55
60			4.17	19.2		17.3		15.4		60
65			3.85	20.8		18.7		16.6		65
70			3.57	22.4		20.2		17.9		70
75			3.33	24.0		21.6		19.2		75
80			3.13	25.6		23.0		20.5		80
90			2.78	28.8		25.9		23.0		90
100			2.50	32.0		28.8		25.6		100
125	2.00	40.0	36.0	32.0	125					
150	1.67	48.0	43.2	38.4	150					

MEDIUM LOAD

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YM22x25	22	11	12.13	8.0	97	7.2	87	6.4	77	25
30			10.10	9.6		8.6		7.7		30
35			8.66	11.2		10.1		9.0		35
40			7.58	12.8		11.5		10.2		40
45			6.74	14.4		13.0		11.5		45
50			6.06	16.0		14.4		12.8		50
55			5.51	17.6		15.8		14.1		55
60			5.05	19.2		17.3		15.4		60
65			4.66	20.8		18.7		16.6		65
70			4.33	22.4		20.2		17.9		70
75			4.04	24.0		21.6		19.2		75
80			3.79	25.6		23.0		20.5		80
90			3.37	28.8		25.9		23.0		90
100			3.03	32.0		28.8		25.6		100
125			2.43	40.0		36.0		32.0		125
150			2.02	48.0		43.2		38.4		150
175			1.73	56.0		50.4		44.8		175
YM25x25	25	12.5	15.63	8.0	125	7.2	112	6.4	100	25
30			13.02	9.6		8.6		7.7		30
35			11.16	11.2		10.1		9.0		35
40			9.77	12.8		11.5		10.2		40
45			8.68	14.4		13.0		11.5		45
50			7.81	16.0		14.4		12.8		50
55			7.10	17.6		15.8		14.1		55
60			6.51	19.2		17.3		15.4		60
65			6.01	20.8		18.7		16.6		65
70			5.58	22.4		20.2		17.9		70
75			5.21	24.0		21.6		19.2		75
80			4.88	25.6		23.0		20.5		80
90			4.34	28.8		25.9		23.0		90
100			3.91	32.0		28.8		25.6		100
125			3.13	40.0		36.0		32.0		125
150			2.60	48.0		43.2		38.4		150
175			2.23	56.0		50.4		44.8		175
200	1.95	64.0	57.6	51.2	200					
YM27x25	27	13.5	18.25	8.0	146	7.2	131	6.4	117	25
30			15.21	9.6		8.6		7.7		30
35			13.04	11.2		10.1		9.0		35
40			11.41	12.8		11.5		10.2		40
45			10.14	14.4		13.0		11.5		45
50			9.13	16.0		14.4		12.8		50
55			8.30	17.6		15.8		14.1		55
60			7.60	19.2		17.3		15.4		60
65			7.02	20.8		18.7		16.6		65
70			6.52	22.4		20.2		17.9		70
75			6.08	24.0		21.6		19.2		75
80			5.70	25.6		23.0		20.5		80
90			5.07	28.8		25.9		23.0		90
100			4.56	32.0		28.8		25.6		100
125			3.65	40.0		36.0		32.0		125
150			3.04	48.0		43.2		38.4		150
175			2.61	56.0		50.4		44.8		175
YM30x25	30	15	22.50	8.0	180	7.2	161	6.4	144	25
30			18.75	9.6		8.6		7.7		30
35			16.07	11.2		10.1		9.0		35
40			14.06	12.8		11.5		10.2		40
45			12.50	14.4		13.0		11.5		45
50			11.25	16.0		14.4		12.8		50
55			10.23	17.6		15.8		14.1		55
60			9.38	19.2		17.3		15.4		60
65			8.65	20.8		18.7		16.6		65
70			8.04	22.4		20.2		17.9		70
75			7.50	24.0		21.6		19.2		75
80			7.03	25.6		23.0		20.5		80
90			6.25	28.8		25.9		23.0		90
100			5.63	32.0		28.8		25.6		100
125			4.50	40.0		36.0		32.0		125
150			3.75	48.0		43.2		38.4		150
175			3.21	56.0		50.4		44.8		175
200	2.81	64.0	57.6	51.2	200					

YM 中荷重

台灣製造

MADE IN TAIWAN

MEDIUM LOAD

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YM35x40	35	17.5	19.14	12.8	245	11.5	220	10.2	195	40
45			17.01	14.4		13.0		11.5		45
50			15.31	16.0		14.4		12.8		50
55			13.92	17.6		15.8		14.1		55
60			12.76	19.2		17.3		15.4		60
65			11.78	20.8		18.7		16.6		65
70			10.94	22.4		20.2		17.9		70
75			10.21	24.0		21.6		19.2		75
80			9.57	25.6		23.0		20.5		80
90			8.51	28.8		25.9		23.0		90
100			7.66	32.0		28.8		25.6		100
125			6.13	40.0		36.0		32.0		125
150			5.10	48.0		43.2		38.4		150
175			4.38	56.0		50.4		44.8		175
200			3.83	64.0		57.6		51.2		200
YM40x40			40	20		25.00		12.8		320
45	22.22	14.4			13.0	11.5	45			
50	20.00	16.0			14.4	12.8	50			
55	18.18	17.6			15.8	14.1	55			
60	16.67	19.2			17.3	15.4	60			
65	15.38	20.8			18.7	16.6	65			
70	14.29	22.4			20.2	17.9	70			
75	13.33	24.0			21.6	19.2	75			
80	12.50	25.6			23.0	20.5	80			
90	11.11	28.8			25.9	23.0	90			
100	10.00	32.0			28.8	25.6	100			
125	8.00	40.0			36.0	32.0	125			
150	6.67	48.0			43.2	38.4	150			
175	5.71	56.0			50.4	44.8	175			
200	5.00	64.0			57.6	51.2	200			
250	4.00	80.0			72.0	64.0	250			
YM50x50	50	25	31.25	16.0	500	14.4	450	12.8	400	50
55			28.41	17.6		15.8		14.1		55
60			26.04	19.2		17.3		15.4		60
65			24.04	20.8		18.7		16.6		65
70			22.32	22.4		20.2		17.9		70
75			20.83	24.0		21.6		19.2		75
80			19.53	25.6		23.0		20.5		80
90			17.36	28.8		25.9		23.0		90
100			15.63	32.0		28.8		25.6		100
125			12.50	40.0		36.0		32.0		125
150			10.42	48.0		43.2		38.4		150
175			8.93	56.0		50.4		44.8		175
200			7.81	64.0		57.6		51.2		200
250			6.25	80.0		72.0		64.0		250
300			5.21	96.0		86.4		76.8		300
YM60x60			60	30		37.50		19.2		720
65	34.62	20.8			18.7	16.6	65			
70	32.14	22.4			20.2	17.9	70			
75	30.00	24.0			21.6	19.2	75			
80	28.13	25.6			23.0	20.5	80			
90	25.00	28.8			25.9	23.0	90			
100	22.50	32.0			28.8	25.6	100			
125	18.00	40.0			36.0	32.0	125			
150	15.00	48.0			43.2	38.4	150			
175	12.86	56.0			50.4	44.8	175			
200	11.25	64.0			57.6	51.2	200			
250	9.00	80.0			72.0	64.0	250			
300	7.50	96.0			86.4	76.8	300			

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YH08x10	8	4	11.67	2.4	28	2.2	25	1.9	22	10
15			7.78	3.6		3.2		2.9		15
20			5.83	4.8		4.3		3.8		20
25			4.67	6.0		5.4		4.8		25
30			3.89	7.2		6.5		5.8		30
35			3.33	8.4		7.6		6.7		35
40			2.92	9.6		8.6		7.7		40
45			2.59	10.8		9.7		8.6		45
50			2.33	12.0		10.8		9.6		50
55			2.12	13.2		11.9		10.6		55
60			1.94	14.4		13.0		11.5		60
65			1.79	15.6		14.0		12.5		65
70			1.67	16.8		15.1		13.4		70
75			1.56	18.0		16.2		14.4		75
80			1.46	19.2		17.3		15.4		80
85			1.37	27.2		24.5		21.8		85
90			1.30	21.6		19.4		17.3		90
95	1.23	30.4	27.4	24.3	95					
100	1.17	24.0	21.6	19.2	100					
YH10x10	10	5	12.50	2.4	30	2.2	27	1.9	24	10
15			8.33	3.6		3.2		2.9		15
20			6.25	4.8		4.3		3.8		20
25			5.00	6.0		5.4		4.8		25
30			4.17	7.2		6.5		5.8		30
35			3.57	8.4		7.6		6.7		35
40			3.13	9.6		8.6		7.7		40
45			2.78	10.8		9.7		8.6		45
50			2.50	12.0		10.8		9.6		50
55			2.27	13.2		11.9		10.6		55
60			2.08	14.4		13.0		11.5		60
65			1.92	15.6		14.0		12.5		65
70			1.79	16.8		15.1		13.4		70
75			1.67	18.0		16.2		14.4		75
80			1.56	19.2		17.3		15.4		80
85			1.47	27.2		24.5		21.8		85
90			1.39	21.6		19.4		17.3		90
95	1.32	30.4	27.4	24.3	95					
100	1.25	24.0	21.6	19.2	100					
YH12x15	12	6	11.94	3.6	43	3.2	38	2.9	34	15
20			8.96	4.8		4.3		3.8		20
25			7.17	6.0		5.4		4.8		25
30			5.97	7.2		6.5		5.8		30
35			5.12	8.4		7.6		6.7		35
40			4.48	9.6		8.6		7.7		40
45			3.98	10.8		9.7		8.6		45
50			3.58	12.0		10.8		9.6		50
55			3.26	13.2		11.9		10.6		55
60			2.99	14.4		13.0		11.5		60
65			2.76	15.6		14.0		12.5		65
70			2.56	16.8		15.1		13.4		70
75			2.39	18.0		16.2		14.4		75
80			2.24	19.2		17.3		15.4		80
85			2.11	27.2		24.5		21.8		85
90			1.99	21.6		19.4		17.3		90
95			1.89	30.4		27.4		24.3		95
100	1.79	24.0	21.6	19.2	100					

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YH25x50=50pcs

交貨日期：現貨供應。

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YH14x20	14	7	12.29	4.8	59	4.3	53	3.8	47	20
25			9.83	6.0		5.4		4.8		25
30			8.19	7.2		6.5		5.8		30
35			7.02	8.4		7.6		6.7		35
40			6.15	9.6		8.6		7.7		40
45			5.46	10.8		9.7		8.6		45
50			4.92	12.0		10.8		9.6		50
55			4.47	13.2		11.9		10.6		55
60			4.10	14.4		13.0		11.5		60
65			3.78	15.6		14.0		12.5		65
70			3.51	16.8		15.1		13.4		70
75			3.28	18.0		16.2		14.4		75
80			3.07	19.2		17.3		15.4		80
90			2.73	21.6		19.4		17.3		90
100			2.46	24.0		21.6		19.2		100
125	4.83	30.0	27.0	24.0	125					
YH16x20	16	8	16.04	4.8	77	4.3	69	3.8	62	20
25			12.83	6.0		5.4		4.8		25
30			10.69	7.2		6.5		5.8		30
35			9.17	8.4		7.6		6.7		35
40			8.02	9.6		8.6		7.7		40
45			7.13	10.8		9.7		8.6		45
50			6.42	12.0		10.8		9.6		50
55			5.83	13.2		11.9		10.6		55
60			5.35	14.4		13.0		11.5		60
65			4.94	15.6		14.0		12.5		65
70			4.58	16.8		15.1		13.4		70
75			4.28	18.0		16.2		14.4		75
80			4.01	19.2		17.3		15.4		80
90			3.56	21.6		19.4		17.3		90
100			3.21	24.0		21.6		19.2		100
125	2.57	30.0	27.0	24.0	125					
YH18x20	18	9	20.21	4.8	97	4.3	87	3.8	78	20
25			16.17	6.0		5.4		4.8		25
30			13.47	7.2		6.5		5.8		30
35			11.55	8.4		7.6		6.7		35
40			10.10	9.6		8.6		7.7		40
45			8.98	10.8		9.7		8.6		45
50			8.08	12.0		10.8		9.6		50
55			7.35	13.2		11.9		10.6		55
60			6.74	14.4		13.0		11.5		60
65			6.22	15.6		14.0		12.5		65
70			5.77	16.8		15.1		13.4		70
75			5.39	18.0		16.2		14.4		75
80			5.05	19.2		17.3		15.4		80
90			4.49	21.6		19.4		17.3		90
100			4.04	24.0		21.6		19.2		100
125	3.23	30.0	27.0	24.0	125					
150	2.69	36.0	32.4	28.8	150					
YH20x20	20	10	25.00	4.8	120	4.3	108	3.8	96	20
25			20.00	6.0		5.4		4.8		25
30			16.67	7.2		6.5		5.8		30
35			14.29	8.4		7.6		6.7		35
40			12.50	9.6		8.6		7.7		40
45			11.11	10.8		9.7		8.6		45
50			10.00	12.0		10.8		9.6		50
55			9.09	13.2		11.9		10.6		55
60			8.33	14.4		13.0		11.5		60
65			7.69	15.6		14.0		12.5		65
70			7.14	16.8		15.1		13.4		70
75			6.67	18.0		16.2		14.4		75
80			6.25	19.2		17.3		15.4		80
90			5.56	21.6		19.4		17.3		90
100			5.00	24.0		21.6		19.2		100
125	4.00	30.0	27.0	24.0	125					
150	3.33	36.0	32.4	28.8	150					

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YH22x25	22	11	24.17	6.0	145	5.4	130	4.8	116	25
30			20.14	7.2		6.5		5.8		30
35			17.26	8.4		7.6		6.7		35
40			15.10	9.6		8.6		7.7		40
45			13.43	10.8		9.7		8.6		45
50			12.08	12.0		10.8		9.6		50
55			10.98	13.2		11.9		10.6		55
60			10.07	14.4		13.0		11.5		60
65			9.29	15.6		14.0		12.5		65
70			8.63	16.8		15.1		13.4		70
75			8.06	18.0		16.2		14.4		75
80			7.55	19.2		17.3		15.4		80
90			6.71	21.6		19.4		17.3		90
100			6.04	24.0		21.6		19.2		100
125			4.83	30.0		27.0		24.0		125
150			4.03	36.0		32.4		28.8		150
175			3.45	42.0		37.8		33.6		175
YH25x25	25	12.5	31.17	6.0	187	5.4	169	4.8	150	25
30			25.97	7.2		6.5		5.8		30
35			22.26	8.4		7.6		6.7		35
40			19.48	9.6		8.6		7.7		40
45			17.31	10.8		9.7		8.6		45
50			15.58	12.0		10.8		9.6		50
55			14.17	13.2		11.9		10.6		55
60			12.99	14.4		13.0		11.5		60
65			11.99	15.6		14.0		12.5		65
70			11.13	16.8		15.1		13.4		70
75			10.39	18.0		16.2		14.4		75
80			9.74	19.2		17.3		15.4		80
90			8.66	21.6		19.4		17.3		90
100			7.79	24.0		21.6		19.2		100
125			6.23	30.0		27.0		24.0		125
150			5.19	36.0		32.4		28.8		150
175			4.45	42.0		37.8		33.6		175
200	3.90	48.0	43.2	38.4	200					
YH27x25	27	13.5	36.50	6.0	219	5.4	197	4.8	175	25
30			30.42	7.2		6.5		5.8		30
35			26.07	8.4		7.6		6.7		35
40			22.81	9.6		8.6		7.7		40
45			20.28	10.8		9.7		8.6		45
50			18.25	12.0		10.8		9.6		50
55			16.59	13.2		11.9		10.6		55
60			15.21	14.4		13.0		11.5		60
65			14.04	15.6		14.0		12.5		65
70			13.04	16.8		15.1		13.4		70
75			12.17	18.0		16.2		14.4		75
80			11.41	19.2		17.3		15.4		80
90			10.14	21.6		19.4		17.3		90
100			9.13	24.0		21.6		19.2		100
125			7.30	30.0		27.0		24.0		125
150			6.08	36.0		32.4		28.8		150
175			5.21	42.0		37.8		33.6		175
200	4.56	48.0	43.2	38.4	200					
YH30x25	30	15	45.00	6.0	270	5.4	243	4.8	216	25
30			37.50	7.2		6.5		5.8		30
35			32.14	8.4		7.6		6.7		35
40			28.13	9.6		8.6		7.7		40
45			25.00	10.8		9.7		8.6		45
50			22.50	12.0		10.8		9.6		50
55			20.45	13.2		11.9		10.6		55
60			18.75	14.4		13.0		11.5		60
65			17.31	15.6		14.0		12.5		65
70			16.07	16.8		15.1		13.4		70
75			15.00	18.0		16.2		14.4		75
80			14.06	19.2		17.3		15.4		80
90			12.50	21.6		19.4		17.3		90
100			11.25	24.0		21.6		19.2		100
125			9.00	30.0		27.0		24.0		125
150			7.50	36.0		32.4		28.8		150
175			6.43	42.0		37.8		33.6		175
200	5.63	48.0	43.2	38.4	200					

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YH35x40	35	17.5	38.23	9.6	367	8.6	330	7.7	293	40
45			33.98	10.8		9.7		8.6		45
50			30.58	12.0		10.8		9.6		50
55			27.80	13.2		11.9		10.6		55
60			25.49	14.4		13.0		11.5		60
65			23.53	15.6		14.0		12.5		65
70			21.85	16.8		15.1		13.4		70
75			20.39	18.0		16.2		14.4		75
80			19.11	19.2		17.3		15.4		80
90			16.99	21.6		19.4		17.3		90
100			15.29	24.0		21.6		19.2		100
125			12.23	30.0		27.0		24.0		125
150			10.19	36.0		32.4		28.8		150
175			8.74	42.0		37.8		33.6		175
200	7.65	48.0	43.2	38.4	200					
YH40x40	40	20	50.00	9.6	480	8.6	432	7.7	384	40
45			44.40	10.8		9.7		8.6		45
50			40.00	12.0		10.8		9.6		50
55			36.40	13.2		11.9		10.6		55
60			33.33	14.4		13.0		11.5		60
65			30.80	15.6		14.0		12.5		65
70			28.57	16.8		15.1		13.4		70
75			26.70	18.0		16.2		14.4		75
80			25.00	19.2		17.3		15.4		80
90			22.22	21.6		19.4		17.3		90
100			20.00	24.0		21.6		19.2		100
125			16.00	30.0		27.0		24.0		125
150			13.33	36.0		32.4		28.8		150
175			11.43	42.0		37.8		33.6		175
200	10.00	48.0	43.2	38.4	200					
250	8.00	60.0	54.0	48.0	250					
YH50x50	50	25	62.50	12.0	750	10.8	675	9.6	600	50
55			56.80	13.2		11.9		10.6		55
60			52.08	14.4		13.0		11.5		60
65			48.10	15.6		14.0		12.5		65
70			44.64	16.8		15.1		13.4		70
75			41.70	18.0		16.2		14.4		75
80			39.06	19.2		17.3		15.4		80
90			34.72	21.6		19.4		17.3		90
100			31.25	24.0		21.6		19.2		100
125			25.00	30.0		27.0		24.0		125
150			20.83	36.0		32.4		28.8		150
175			17.86	42.0		37.8		33.6		175
200			15.63	48.0		43.2		38.4		200
250			12.50	60.0		54.0		48.0		250
300	10.42	72.0	64.8	57.6	300					
YH60x60	60	30	75.00	14.4	1080	13.0	973	11.5	864	60
65			69.20	15.6		14.0		12.5		65
70			64.29	16.8		15.1		13.4		70
75			60.00	18.0		16.2		14.4		75
80			56.25	19.2		17.3		15.4		80
90			50.00	21.6		19.4		17.3		90
100			45.00	24.0		21.6		19.2		100
125			36.00	30.0		27.0		24.0		125
150			30.00	36.0		32.4		28.8		150
175			25.71	42.0		37.8		33.6		175
200			22.50	48.0		43.2		38.4		200
250			18.00	60.0		54.0		48.0		250
300			15.00	72.0		64.8		57.6		300

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YH25x50=50pcs

交貨日期：現貨供應。

YB 極重荷重

台灣製造

MADE IN TAIWAN

SUPER LOAD

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YB08x10	8	4	16.50	2.0	33	1.8	30	1.6	26	10
15			11.00	3.0		2.7		2.4		15
20			8.25	4.0		3.6		3.2		20
25			6.60	5.0		4.5		4.0		25
30			5.50	6.0		5.4		4.8		30
35			4.71	7.0		6.3		5.6		35
40			4.13	8.0		7.2		6.4		40
45			3.67	9.0		8.1		7.2		45
50			3.30	10.0		9.0		8.0		50
55			3.00	11.0		9.9		8.8		55
60			2.75	12.0		10.8		9.6		60
65			2.54	13.0		11.7		10.4		65
70			2.36	14.0		12.6		11.2		70
75			2.20	15.0		13.5		12.0		75
80			2.06	16.0		14.4		12.8		80
90			1.83	18.0		16.2		14.4		90
100			1.65	20.0		18.0		16.0		100
YB10x10	10	5	22.50	2.0	45	1.8	41	1.6	36	10
15			15.00	3.0		2.7		2.4		15
20			11.25	4.0		3.6		3.2		20
25			9.00	5.0		4.5		4.0		25
30			7.50	6.0		5.4		4.8		30
35			6.43	7.0		6.3		5.6		35
40			5.63	8.0		7.2		6.4		40
45			5.00	9.0		8.1		7.2		45
50			4.50	10.0		9.0		8.0		50
55			4.09	11.0		9.9		8.8		55
60			3.75	12.0		10.8		9.6		60
65			3.46	13.0		11.7		10.4		65
70			3.21	14.0		12.6		11.2		70
75			3.00	15.0		13.5		12.0		75
80			2.81	16.0		14.4		12.8		80
90			2.50	18.0		16.2		14.4		90
100			2.25	20.0		18.0		16.0		100
YB12x15	12	6	19.33	3.0	58	2.7	52	2.4	46	15
20			14.50	4.0		3.6		3.2		20
25			11.60	5.0		4.5		4.0		25
30			9.67	6.0		5.4		4.8		30
35			8.29	7.0		6.3		5.6		35
40			7.25	8.0		7.2		6.4		40
45			6.44	9.0		8.1		7.2		45
50			5.80	10.0		9.0		8.0		50
55			5.27	11.0		9.9		8.8		55
60			4.83	12.0		10.8		9.6		60
65			4.46	13.0		11.7		10.4		65
70			4.14	14.0		12.6		11.2		70
75			3.87	15.0		13.5		12.0		75
80			3.63	16.0		14.4		12.8		80
90			3.22	18.0		16.2		14.4		90
100			2.90	20.0		18.0		16.0		100

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YB25x50=50pcs

交貨日期：現貨供應。

YB 極重荷重

台灣製造

MADE IN TAIWAN

SUPER LOAD

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30万 0.3million		50万 0.5million		100万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YB14x20	14	7	18.75	4.0	75	3.6	68	3.2	60	20
25			15.00	5.0		4.5		4.0		25
30			12.50	6.0		5.4		4.8		30
35			10.71	7.0		6.3		5.6		35
40			9.38	8.0		7.2		6.4		40
45			8.33	9.0		8.1		7.2		45
50			7.50	10.0		9.0		8.0		50
55			6.82	11.0		9.9		8.8		55
60			6.25	12.0		10.8		9.6		60
65			5.77	13.0		11.7		10.4		65
70			5.36	14.0		12.6		11.2		70
75			5.00	15.0		13.5		12.0		75
80			4.69	16.0		14.4		12.8		80
90			4.17	18.0		16.2		14.4		90
100			3.75	20.0		18.0		16.0		100
125	3.00	25.0	22.5	20.0	125					
YB16x20	16	8	25.00	4.0	100	3.6	90	3.2	80	20
25			20.00	5.0		4.5		4.0		25
30			16.67	6.0		5.4		4.8		30
35			14.29	7.0		6.3		5.6		35
40			12.50	8.0		7.2		6.4		40
45			11.11	9.0		8.1		7.2		45
50			10.00	10.0		9.0		8.0		50
55			9.09	11.0		9.9		8.8		55
60			8.33	12.0		10.8		9.6		60
65			7.69	13.0		11.7		10.4		65
70			7.14	14.0		12.6		11.2		70
75			6.67	15.0		13.5		12.0		75
80			6.25	16.0		14.4		12.8		80
90			5.56	18.0		16.2		14.4		90
100			5.00	20.0		18.0		16.0		100
125	4.00	25.0	22.5	20.0	125					
YB18x25	18	9	25.00	5.0	125	4.5	113	4.0	100	25
30			20.83	6.0		5.4		4.8		30
35			17.86	7.0		6.3		5.6		35
40			15.63	8.0		7.2		6.4		40
45			13.89	9.0		8.1		7.2		45
50			12.50	10.0		9.0		8.0		50
55			11.36	11.0		9.9		8.8		55
60			10.42	12.0		10.8		9.6		60
65			9.62	13.0		11.7		10.4		65
70			8.93	14.0		12.6		11.2		70
75			8.33	15.0		13.5		12.0		75
80			7.81	16.0		14.4		12.8		80
90			6.94	18.0		16.2		14.4		90
100			6.25	20.0		18.0		16.0		100
125			5.00	25.0		22.5		20.0		125
YB20x 20	20	10	40.00	4.0	160	3.6	144	3.2	128	20
25			32.00	5.0		4.5		4.0		25
30			26.67	6.0		5.4		4.8		30
35			22.86	7.0		6.3		5.6		35
40			20.00	8.0		7.2		6.4		40
45			17.78	9.0		8.1		7.2		45
50			16.00	10.0		9.0		8.0		50
55			14.55	11.0		9.9		8.8		55
60			13.33	12.0		10.8		9.6		60
65			12.31	13.0		11.7		10.4		65
70			11.43	14.0		12.6		11.2		70
75			10.67	15.0		13.5		12.0		75
80			10.00	16.0		14.4		12.8		80
90			8.89	18.0		16.2		14.4		90
100			8.00	20.0		18.0		16.0		100
125	6.40	25.0	22.5	20.0	125					
150	6.50	30.0	27.0	24.0	150					

YB 極重荷重

SUPER LOAD

台灣製造

MADE IN TAIWAN

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30万 0.3million		50万 0.5million		100万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YB22x25	22	11	39.00	5.0	195	4.5	176	4.0	156	25
30			32.50	6.0		5.4		4.8		30
35			27.86	7.0		6.3		5.6		35
40			24.38	8.0		7.2		6.4		40
45			21.67	9.0		8.1		7.2		45
50			19.50	10.0		9.0		8.0		50
55			17.73	11.0		9.9		8.8		55
60			16.25	12.0		10.8		9.6		60
65			15.00	13.0		11.7		10.4		65
70			13.93	14.0		12.6		11.2		70
75			13.00	15.0		13.5		12.0		75
80			12.19	16.0		14.4		12.8		80
90			10.83	18.0		16.2		14.4		90
100			9.75	20.0		18.0		16.0		100
125			7.80	25.0		22.5		20.0		125
150	6.50	30.0	27.0	24.0	150					
YB25x25	25	12.5	49.00	5.0	245	4.5	221	4.0	196	25
30			40.83	6.0		5.4		4.8		30
35			35.00	7.0		6.3		5.6		35
40			30.63	8.0		7.2		6.4		40
45			27.22	9.0		8.1		7.2		45
50			24.50	10.0		9.0		8.0		50
55			22.27	11.0		9.9		8.8		55
60			20.42	12.0		10.8		9.6		60
65			18.85	13.0		11.7		10.4		65
70			17.50	14.0		12.6		11.2		70
75			16.33	15.0		13.5		12.0		75
80			15.31	16.0		14.4		12.8		80
90			13.61	18.0		16.2		14.4		90
100			12.25	20.0		18.0		16.0		100
125			9.80	25.0		22.5		20.0		125
150	8.17	30.0	27.0	24.0	150					
175	7.00	35.0	31.5	28.0	175					
YB27x25	27	13.5	58.00	5.0	290	4.5	261	4.0	232	25
30			48.33	6.0		5.4		4.8		30
35			41.43	7.0		6.3		5.6		35
40			36.25	8.0		7.2		6.4		40
45			32.22	9.0		8.1		7.2		45
50			29.00	10.0		9.0		8.0		50
55			26.36	11.0		9.9		8.8		55
60			24.17	12.0		10.8		9.6		60
65			22.31	13.0		11.7		10.4		65
70			20.71	14.0		12.6		11.2		70
75			19.33	15.0		13.5		12.0		75
80			18.13	16.0		14.4		12.8		80
90			16.11	18.0		16.2		14.4		90
100			14.50	20.0		18.0		16.0		100
125			11.60	25.0		22.5		20.0		125
150	9.67	30.0	27.0	24.0	150					
175	8.29	35.0	31.5	28.0	175					
YB30X25	30	15	72.00	5.0	360	4.5	324	4.0	288	25
30			60.00	6.0		5.4		4.8		30
35			51.43	7.0		6.3		5.6		35
40			45.00	8.0		7.2		6.4		40
45			40.00	9.0		8.1		7.2		45
50			36.00	10.0		9.0		8.0		50
55			32.73	11.0		9.9		8.8		55
60			30.00	12.0		10.8		9.6		60
65			27.69	13.0		11.7		10.4		65
70			25.71	14.0		12.6		11.2		70
75			24.00	15.0		13.5		12.0		75
80			22.50	16.0		14.4		12.8		80
90			20.00	18.0		16.2		14.4		90
100			18.00	20.0		18.0		16.0		100
125			14.40	25.0		22.5		20.0		125
150	12.00	30.0	27.0	24.0	150					
175	10.29	35.0	31.5	28.0	175					
200	9.00	40.0	36.0	32.0	200					

YB 極重荷重

台灣製造

MADE IN TAIWAN

SUPER LOAD

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30万 0.3million		50万 0.5million		100万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YB35x40	35	17.5	61.25	8.0	490	7.2	441	6.4	392	40
45			54.44	9.0		8.1		7.2		45
50			49.00	10.0		9.0		8.0		50
55			44.55	11.0		9.9		8.8		55
60			40.83	12.0		10.8		9.6		60
65			37.69	13.0		11.7		10.4		65
70			35.00	14.0		12.6		11.2		70
75			32.67	15.0		13.5		12.0		75
80			30.63	16.0		14.4		12.8		80
90			27.22	18.0		16.2		14.4		90
100			24.50	20.0		18.0		16.0		100
125			19.60	25.0		22.5		20.0		125
150			16.33	30.0		27.0		24.0		150
175			14.00	35.0		31.5		28.0		175
200			12.25	40.0		36.0		32.0		200
YB40X40	40	20	80.00	8.0	640	7.2	576	6.4	512	40
45			71.11	9.0		8.1		7.2		45
50			64.00	10.0		9.0		8.0		50
55			58.18	11.0		9.9		8.8		55
60			53.33	12.0		10.8		9.6		60
65			49.23	13.0		11.7		10.4		65
70			45.71	14.0		12.6		11.2		70
75			42.67	15.0		13.5		12.0		75
80			40.00	16.0		14.4		12.8		80
90			35.56	18.0		16.2		14.4		90
100			32.00	20.0		18.0		16.0		100
125			25.60	25.0		22.5		20.0		125
150			21.33	30.0		27.0		24.0		150
175			18.29	35.0		31.5		28.0		175
200			16.00	40.0		36.0		32.0		200
250	12.80	50.0	45.0	40.0	250					
YB50x50	50	25	100.00	10.0	1000	9.0	900	8.0	800	50
55			90.91	11.0		9.9		8.8		55
60			83.33	12.0		10.8		9.6		60
65			76.92	13.0		11.7		10.4		65
70			71.43	14.0		12.6		11.2		70
75			66.67	15.0		13.5		12.0		75
80			62.50	16.0		14.4		12.8		80
90			55.56	18.0		16.2		14.4		90
100			50.00	20.0		18.0		16.0		100
125			40.00	25.0		22.5		20.0		125
150			33.33	30.0		27.0		24.0		150
175			28.57	35.0		31.5		28.0		175
200			25.00	40.0		36.0		32.0		200
250			20.00	50.0		45.0		40.0		250
300			16.67	60.0		54.0		48.0		300
YB60x90	60	30	80.00	18.0	1440	16.2	1296	14.4	1152	90
100			72.00	20.0		18.0		16.0		100
125			57.60	25.0		22.5		20.0		125
150			48.00	30.0		27.0		24.0		150
175			41.14	35.0		31.5		28.0		175
200			36.00	40.0		36.0		32.0		200
250			28.80	50.0		45.0		40.0		250
300			24.00	60.0		54.0		48.0		300

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YB25x50=50pcs

交貨日期：現貨供應。

LR JIS 圓綫彈簧

JIS ROUND COIL SPRING

台灣製造
MADE IN TAIWAN

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	16%		24%		32%		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
LR06X15	6	4	0.75	2.4	1.8	3.6	2.7	4.8	3.6	15
20			0.56	3.2		4.8		6.4		20
25			0.45	4.0		6.0		8.0		25
30			0.38	4.8		7.2		9.6		30
35			0.32	5.6		8.4		11.2		35
LR08x15			8	5.4		1.33		2.4		3.2
20	1.00	3.2			4.8	6.4	20			
25	0.80	4.0			6.0	8.0	25			
30	0.67	4.8			7.2	9.6	30			
35	0.57	5.6			8.4	11.2	35			
40	0.50	6.4			9.6	12.8	40			
LR10x25	10	6.5	1.25	4.0	5	6.0	7.5	8.0	10	25
30			1.04	4.8		7.2		9.6		30
35			0.89	5.6		8.4		11.2		35
40			0.78	6.4		9.6		12.8		40
45			0.69	7.2		10.8		14.4		45
50			0.63	8.0		12.0		16.0		50
55			0.57	8.8		13.2		17.6		55
60			0.52	9.6		14.4		19.2		60
LR16X25			16	10.7		3.20		4.0		12.8
30	2.67	4.8			7.2	9.6	30			
35	2.29	5.6			8.4	11.2	35			
40	2.00	6.4			9.6	12.8	40			
45	1.78	7.2			10.8	14.4	45			
50	1.60	8.0			12.0	16.0	50			
55	1.45	8.8			13.2	17.6	55			
60	1.33	9.6			14.4	19.2	60			
65	1.23	10.4			15.6	20.8	65			
70	1.14	11.2			16.8	22.4	70			
75	1.07	12.0			18.0	24.0	75			
80	1.00	12.8	19.2	25.6	80					
LR18X25	18	12	4.05	4.0	16.2	6.0	24.3	8.0	32.4	25
30			3.38	4.8		7.2		9.6		30
35			2.89	5.6		8.4		11.2		35
40			2.53	6.4		9.6		12.8		40
45			2.25	7.2		10.8		14.4		45
50			2.03	8.0		12.0		16.0		50
55			1.84	8.8		13.2		17.6		55
60			1.69	9.6		14.4		19.2		60
65			1.56	10.4		15.6		20.8		65
70			1.45	11.2		16.8		22.4		70
75			1.35	12.0		18.0		24.0		75
80	1.27	12.8	19.2	25.6	80					
90	1.13	14.4	21.6	28.8	90					

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：LR25x50=50pcs

交貨日期：現貨供應。

LR JIS 圓綫彈簧

JIS ROUND COIL SPRING

台灣製造
MADE IN TAIWAN

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	16%		24%		32%		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
LR20X25	20	13.5	5.00	4.0	20	6.0	30	8.0	40	25
30			4.17	4.8		7.2		9.6		30
35			3.57	5.6		8.4		11.2		35
40			3.13	6.4		9.6		12.8		40
45			2.78	7.2		10.8		14.4		45
50			2.50	8.0		12.0		16.0		50
55			2.27	8.8		13.2		17.6		55
60			2.08	9.6		14.4		19.2		60
65			1.92	10.4		15.6		20.8		65
70			1.79	11.2		16.8		22.4		70
75			1.67	12.0		18.0		24.0		75
80			1.56	12.8		19.2		25.6		80
90			1.39	14.4		21.6		28.8		90
100			1.25	16.0		24.0		32.0		100
LR22X25	22	14.7	6.05	4.0	24.2	6.0	36.3	8.0	48.4	25
30			5.04	4.8		7.2		9.6		30
35			4.32	5.6		8.4		11.2		35
40			3.78	6.4		9.6		12.8		40
45			3.36	7.2		10.8		14.4		45
50			3.03	8.0		12.0		16.0		50
55			2.75	8.8		13.2		17.6		55
60			2.52	9.6		14.4		19.2		60
65			2.33	10.4		15.6		20.8		65
70			2.16	11.2		16.8		22.4		70
75			2.02	12.0		18.0		24.0		75
80			1.89	12.8		19.2		25.6		80
90			1.68	14.4		21.6		28.8		90
100			1.51	16.0		24.0		32.0		100
LR25X25	25	17	7.83	4.0	31.3	6.0	47	8.0	62.2	25
30			6.52	4.8		7.2		9.6		30
35			5.59	5.6		8.4		11.2		35
40			4.89	6.4		9.6		12.8		40
45			4.35	7.2		10.8		14.4		45
50			3.91	8.0		12.0		16.0		50
55			3.56	8.8		13.2		17.6		55
60			3.26	9.6		14.4		19.2		60
65			3.01	10.4		15.6		20.8		65
70			2.79	11.2		16.8		22.4		70
75			2.61	12.0		18.0		24.0		75
80			2.45	12.8		19.2		25.6		80
90			2.17	14.4		21.6		28.8		90
100			1.96	16.0		24.0		32.0		100
125	1.57	20.0	30.0	40.0	125					
150	1.30	24.0	36.0	48.0	150					
LR30x45	30	21	6.67	7.2	48	10.8	72	14.4	96	45
50			6.00	8.0		12.0		16.0		50
60			5.00	9.6		14.4		19.2		60
70			4.29	11.2		16.8		22.4		70
80			3.75	12.8		19.2		25.6		80
90			3.33	14.4		21.6		28.8		90
100			3.00	16.0		24.0		32.0		100
125			2.40	20.0		30.0		40.0		125
150			2.00	24.0		36.0		48.0		150

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：LR25x50=50pcs

交貨日期：現貨供應。