

YB 極重荷重

台灣製造

MADE IN TAIWAN

SUPER LOAD

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YB08x10	8	4	16.50	2.0	33	1.8	30	1.6	26	10
15			11.00	3.0		2.7		2.4		15
20			8.25	4.0		3.6		3.2		20
25			6.60	5.0		4.5		4.0		25
30			5.50	6.0		5.4		4.8		30
35			4.71	7.0		6.3		5.6		35
40			4.13	8.0		7.2		6.4		40
45			3.67	9.0		8.1		7.2		45
50			3.30	10.0		9.0		8.0		50
55			3.00	11.0		9.9		8.8		55
60			2.75	12.0		10.8		9.6		60
65			2.54	13.0		11.7		10.4		65
70			2.36	14.0		12.6		11.2		70
75			2.20	15.0		13.5		12.0		75
80			2.06	16.0		14.4		12.8		80
90			1.83	18.0		16.2		14.4		90
100			1.65	20.0		18.0		16.0		100
YB10x10	10	5	22.50	2.0	45	1.8	41	1.6	36	10
15			15.00	3.0		2.7		2.4		15
20			11.25	4.0		3.6		3.2		20
25			9.00	5.0		4.5		4.0		25
30			7.50	6.0		5.4		4.8		30
35			6.43	7.0		6.3		5.6		35
40			5.63	8.0		7.2		6.4		40
45			5.00	9.0		8.1		7.2		45
50			4.50	10.0		9.0		8.0		50
55			4.09	11.0		9.9		8.8		55
60			3.75	12.0		10.8		9.6		60
65			3.46	13.0		11.7		10.4		65
70			3.21	14.0		12.6		11.2		70
75			3.00	15.0		13.5		12.0		75
80			2.81	16.0		14.4		12.8		80
90			2.50	18.0		16.2		14.4		90
100			2.25	20.0		18.0		16.0		100
YB12x15	12	6	19.33	3.0	58	2.7	52	2.4	46	15
20			14.50	4.0		3.6		3.2		20
25			11.60	5.0		4.5		4.0		25
30			9.67	6.0		5.4		4.8		30
35			8.29	7.0		6.3		5.6		35
40			7.25	8.0		7.2		6.4		40
45			6.44	9.0		8.1		7.2		45
50			5.80	10.0		9.0		8.0		50
55			5.27	11.0		9.9		8.8		55
60			4.83	12.0		10.8		9.6		60
65			4.46	13.0		11.7		10.4		65
70			4.14	14.0		12.6		11.2		70
75			3.87	15.0		13.5		12.0		75
80			3.63	16.0		14.4		12.8		80
90			3.22	18.0		16.2		14.4		90
100			2.90	20.0		18.0		16.0		100

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YB25x50=50pcs

交貨日期：現貨供應。

YB 極重荷重

台灣製造

MADE IN TAIWAN

SUPER LOAD

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YB14x20	14	7	18.75	4.0	75	3.6	68	3.2	60	20
25			15.00	5.0		4.5		4.0		25
30			12.50	6.0		5.4		4.8		30
35			10.71	7.0		6.3		5.6		35
40			9.38	8.0		7.2		6.4		40
45			8.33	9.0		8.1		7.2		45
50			7.50	10.0		9.0		8.0		50
55			6.82	11.0		9.9		8.8		55
60			6.25	12.0		10.8		9.6		60
65			5.77	13.0		11.7		10.4		65
70			5.36	14.0		12.6		11.2		70
75			5.00	15.0		13.5		12.0		75
80			4.69	16.0		14.4		12.8		80
90			4.17	18.0		16.2		14.4		90
100			3.75	20.0		18.0		16.0		100
125	3.00	25.0	22.5	20.0	125					
YB16x20	16	8	25.00	4.0	100	3.6	90	3.2	80	20
25			20.00	5.0		4.5		4.0		25
30			16.67	6.0		5.4		4.8		30
35			14.29	7.0		6.3		5.6		35
40			12.50	8.0		7.2		6.4		40
45			11.11	9.0		8.1		7.2		45
50			10.00	10.0		9.0		8.0		50
55			9.09	11.0		9.9		8.8		55
60			8.33	12.0		10.8		9.6		60
65			7.69	13.0		11.7		10.4		65
70			7.14	14.0		12.6		11.2		70
75			6.67	15.0		13.5		12.0		75
80			6.25	16.0		14.4		12.8		80
90			5.56	18.0		16.2		14.4		90
100			5.00	20.0		18.0		16.0		100
125	4.00	25.0	22.5	20.0	125					
YB18x25	18	9	25.00	5.0	125	4.5	113	4.0	100	25
30			20.83	6.0		5.4		4.8		30
35			17.86	7.0		6.3		5.6		35
40			15.63	8.0		7.2		6.4		40
45			13.89	9.0		8.1		7.2		45
50			12.50	10.0		9.0		8.0		50
55			11.36	11.0		9.9		8.8		55
60			10.42	12.0		10.8		9.6		60
65			9.62	13.0		11.7		10.4		65
70			8.93	14.0		12.6		11.2		70
75			8.33	15.0		13.5		12.0		75
80			7.81	16.0		14.4		12.8		80
90			6.94	18.0		16.2		14.4		90
100			6.25	20.0		18.0		16.0		100
125			5.00	25.0		22.5		20.0		125
YB20x 20	20	10	40.00	4.0	160	3.6	144	3.2	128	20
25			32.00	5.0		4.5		4.0		25
30			26.67	6.0		5.4		4.8		30
35			22.86	7.0		6.3		5.6		35
40			20.00	8.0		7.2		6.4		40
45			17.78	9.0		8.1		7.2		45
50			16.00	10.0		9.0		8.0		50
55			14.55	11.0		9.9		8.8		55
60			13.33	12.0		10.8		9.6		60
65			12.31	13.0		11.7		10.4		65
70			11.43	14.0		12.6		11.2		70
75			10.67	15.0		13.5		12.0		75
80			10.00	16.0		14.4		12.8		80
90			8.89	18.0		16.2		14.4		90
100			8.00	20.0		18.0		16.0		100
125	6.40	25.0	22.5	20.0	125					
150	6.50	30.0	27.0	24.0	150					

YB 極重荷重

台灣製造

MADE IN TAIWAN

SUPER LOAD

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YB22x25	22	11	39.00	5.0	195	4.5	176	4.0	156	25
30			32.50	6.0		5.4		4.8		30
35			27.86	7.0		6.3		5.6		35
40			24.38	8.0		7.2		6.4		40
45			21.67	9.0		8.1		7.2		45
50			19.50	10.0		9.0		8.0		50
55			17.73	11.0		9.9		8.8		55
60			16.25	12.0		10.8		9.6		60
65			15.00	13.0		11.7		10.4		65
70			13.93	14.0		12.6		11.2		70
75			13.00	15.0		13.5		12.0		75
80			12.19	16.0		14.4		12.8		80
90			10.83	18.0		16.2		14.4		90
100			9.75	20.0		18.0		16.0		100
125			7.80	25.0		22.5		20.0		125
150	6.50	30.0	27.0	24.0	150					
YB25x25	25	12.5	49.00	5.0	245	4.5	221	4.0	196	25
30			40.83	6.0		5.4		4.8		30
35			35.00	7.0		6.3		5.6		35
40			30.63	8.0		7.2		6.4		40
45			27.22	9.0		8.1		7.2		45
50			24.50	10.0		9.0		8.0		50
55			22.27	11.0		9.9		8.8		55
60			20.42	12.0		10.8		9.6		60
65			18.85	13.0		11.7		10.4		65
70			17.50	14.0		12.6		11.2		70
75			16.33	15.0		13.5		12.0		75
80			15.31	16.0		14.4		12.8		80
90			13.61	18.0		16.2		14.4		90
100			12.25	20.0		18.0		16.0		100
125			9.80	25.0		22.5		20.0		125
150	8.17	30.0	27.0	24.0	150					
175	7.00	35.0	31.5	28.0	175					
YB27x25	27	13.5	58.00	5.0	290	4.5	261	4.0	232	25
30			48.33	6.0		5.4		4.8		30
35			41.43	7.0		6.3		5.6		35
40			36.25	8.0		7.2		6.4		40
45			32.22	9.0		8.1		7.2		45
50			29.00	10.0		9.0		8.0		50
55			26.36	11.0		9.9		8.8		55
60			24.17	12.0		10.8		9.6		60
65			22.31	13.0		11.7		10.4		65
70			20.71	14.0		12.6		11.2		70
75			19.33	15.0		13.5		12.0		75
80			18.13	16.0		14.4		12.8		80
90			16.11	18.0		16.2		14.4		90
100			14.50	20.0		18.0		16.0		100
125			11.60	25.0		22.5		20.0		125
150	9.67	30.0	27.0	24.0	150					
175	8.29	35.0	31.5	28.0	175					
YB30X25	30	15	72.00	5.0	360	4.5	324	4.0	288	25
30			60.00	6.0		5.4		4.8		30
35			51.43	7.0		6.3		5.6		35
40			45.00	8.0		7.2		6.4		40
45			40.00	9.0		8.1		7.2		45
50			36.00	10.0		9.0		8.0		50
55			32.73	11.0		9.9		8.8		55
60			30.00	12.0		10.8		9.6		60
65			27.69	13.0		11.7		10.4		65
70			25.71	14.0		12.6		11.2		70
75			24.00	15.0		13.5		12.0		75
80			22.50	16.0		14.4		12.8		80
90			20.00	18.0		16.2		14.4		90
100			18.00	20.0		18.0		16.0		100
125			14.40	25.0		22.5		20.0		125
150	12.00	30.0	27.0	24.0	150					
175	10.29	35.0	31.5	28.0	175					
200	9.00	40.0	36.0	32.0	200					

YB 極重荷重

台灣製造

SUPER LOAD

MADE IN TAIWAN

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30万 0.3million		50万 0.5million		100万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YB35x40	35	17.5	61.25	8.0	490	7.2	441	6.4	392	40
45			54.44	9.0		8.1		7.2		45
50			49.00	10.0		9.0		8.0		50
55			44.55	11.0		9.9		8.8		55
60			40.83	12.0		10.8		9.6		60
65			37.69	13.0		11.7		10.4		65
70			35.00	14.0		12.6		11.2		70
75			32.67	15.0		13.5		12.0		75
80			30.63	16.0		14.4		12.8		80
90			27.22	18.0		16.2		14.4		90
100			24.50	20.0		18.0		16.0		100
125			19.60	25.0		22.5		20.0		125
150			16.33	30.0		27.0		24.0		150
175			14.00	35.0		31.5		28.0		175
200			12.25	40.0		36.0		32.0		200
YB40X40	40	20	80.00	8.0	640	7.2	576	6.4	512	40
45			71.11	9.0		8.1		7.2		45
50			64.00	10.0		9.0		8.0		50
55			58.18	11.0		9.9		8.8		55
60			53.33	12.0		10.8		9.6		60
65			49.23	13.0		11.7		10.4		65
70			45.71	14.0		12.6		11.2		70
75			42.67	15.0		13.5		12.0		75
80			40.00	16.0		14.4		12.8		80
90			35.56	18.0		16.2		14.4		90
100			32.00	20.0		18.0		16.0		100
125			25.60	25.0		22.5		20.0		125
150			21.33	30.0		27.0		24.0		150
175			18.29	35.0		31.5		28.0		175
200			16.00	40.0		36.0		32.0		200
250	12.80	50.0	45.0	40.0	250					
YB50x50	50	25	100.00	10.0	1000	9.0	900	8.0	800	50
55			90.91	11.0		9.9		8.8		55
60			83.33	12.0		10.8		9.6		60
65			76.92	13.0		11.7		10.4		65
70			71.43	14.0		12.6		11.2		70
75			66.67	15.0		13.5		12.0		75
80			62.50	16.0		14.4		12.8		80
90			55.56	18.0		16.2		14.4		90
100			50.00	20.0		18.0		16.0		100
125			40.00	25.0		22.5		20.0		125
150			33.33	30.0		27.0		24.0		150
175			28.57	35.0		31.5		28.0		175
200			25.00	40.0		36.0		32.0		200
250			20.00	50.0		45.0		40.0		250
300			16.67	60.0		54.0		48.0		300
YB60x90	60	30	80.00	18.0	1440	16.2	1296	14.4	1152	90
100			72.00	20.0		18.0		16.0		100
125			57.60	25.0		22.5		20.0		125
150			48.00	30.0		27.0		24.0		150
175			41.14	35.0		31.5		28.0		175
200			36.00	40.0		36.0		32.0		200
250			28.80	50.0		45.0		40.0		250
300			24.00	60.0		54.0		48.0		300

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YB25x50=50pcs

交貨日期：現貨供應。