

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YL08x10	8	4	3.75	4.0	15	3.6	13	3.2	12	10
15			2.50	6.0		5.4		4.8		15
20			1.88	8.0		7.2		6.4		20
25			1.50	10.0		9.0		8.0		25
30			1.25	12.0		10.8		9.6		30
35			1.07	14.0		12.6		11.2		35
40			0.94	16.0		14.4		12.8		40
45			0.83	18.0		16.2		14.4		45
50			0.75	20.0		18.0		16.0		50
55			0.68	22.0		19.8		17.6		55
60			0.63	24.0		21.6		19.2		60
65			0.58	26.0		23.4		20.8		65
70			0.54	28.0		25.2		22.4		70
75			0.50	30.0		27.0		24.0		75
80			0.47	32.0		28.8		25.6		80
85			0.44	34.0		30.6		27.2		85
90			0.42	36.0		32.4		28.8		90
95			0.39	38.0		34.2		30.4		95
100			0.38	40.0		36.0		32.0		100
YL10x10			10	5.5		3.50		4.0		14
15	2.33	6.0			5.4	4.8	15			
20	1.75	8.0			7.2	6.4	20			
25	1.40	10.0			9.0	8.0	25			
30	1.17	12.0			10.8	9.6	30			
35	1.00	14.0			12.6	11.2	35			
40	0.88	16.0			14.4	12.8	40			
45	0.78	18.0			16.2	14.4	45			
50	0.70	20.0			18.0	16.0	50			
55	0.64	22.0			19.8	17.6	55			
60	0.58	24.0			21.6	19.2	60			
65	0.54	26.0			23.4	20.8	65			
70	0.50	28.0			25.2	22.4	70			
75	0.47	30.0			27.0	24.0	75			
80	0.44	32.0			28.8	25.6	80			
85	0.41	34.0			30.6	27.2	85			
90	0.39	36.0			32.4	28.8	90			
95	0.37	38.0			34.2	30.4	95			
100	0.35	40.0			36.0	32.0	100			
YL12x15	12	6.5			3.50	6.0	21	5.4	19	
20			2.63	8.0	7.2	6.4		20		
25			2.10	10.0	9.0	8.0		25		
30			1.75	12.0	10.8	9.6		30		
35			1.50	14.0	12.6	11.2		35		
40			1.31	16.0	14.4	12.8		40		
45			1.17	18.0	16.2	14.4		45		
50			1.05	20.0	18.0	16.0		50		
55			0.95	22.0	19.8	17.6		55		
60			0.88	24.0	21.6	19.2		60		
65			0.81	26.0	23.4	20.8		65		
70			0.75	28.0	25.2	22.4		70		
75			0.70	30.0	27.0	24.0		75		
80			0.66	32.0	28.8	25.6		80		
90			0.59	36.0	32.4	28.8		90		
100			0.53	40.0	36.0	32.0		100		

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YL25x50=50pcs

交貨日期：現貨供應。

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YL14x20	14	7	3.50	8.0	28	7.2	25	6.4	22	20
25			2.80	10.0		9.0		8.0		25
30			2.33	12.0		10.8		9.6		30
35			2.00	14.0		12.6		11.2		35
40			1.75	16.0		14.4		12.8		40
45			1.56	18.0		16.2		14.4		45
50			1.40	20.0		18.0		16.0		50
55			1.27	22.0		19.8		17.6		55
60			1.17	24.0		21.6		19.2		60
65			1.08	26.0		23.4		20.8		65
70			1.00	28.0		25.2		22.4		70
75			0.93	30.0		27.0		24.0		75
80			0.88	32.0		28.8		25.6		80
85			0.82	34.0		30.6		27.2		85
90			0.78	36.0		32.4		28.8		90
100	0.70	40	36.0	32.0	100					
125	0.56	50.0	45.0	40.0	125					
YL16x20	16	8	4.38	8.0	35	7.2	32	6.4	28	20
25			3.50	10.0		9.0		8.0		25
30			2.92	12.0		10.8		9.6		30
35			2.50	14.0		12.6		11.2		35
40			2.19	16.0		14.4		12.8		40
45			1.94	18.0		16.2		14.4		45
50			1.75	20.0		18.0		16.0		50
55			1.59	22.0		19.8		17.6		55
60			1.46	24.0		21.6		19.2		60
65			1.35	26.0		23.4		20.8		65
70			1.25	28.0		25.2		22.4		70
75			1.17	30.0		27.0		24.0		75
80			1.09	32.0		28.8		25.6		80
85			1.03	34.0		30.6		27.2		85
90			0.97	36.0		32.4		28.8		90
100	0.88	40.0	36.0	32.0	100					
125	0.70	50.0	45.0	40.0	125					
YL18x20	18	9	5.38	8.0	43	7.2	39	6.4	34	20
25			4.30	10.0		9.0		8.0		25
30			3.58	12.0		10.8		9.6		30
35			3.07	14.0		12.6		11.2		35
40			2.69	16.0		14.4		12.8		40
45			2.39	18.0		16.2		14.4		45
50			2.15	20.0		18.0		16.0		50
55			1.95	22.0		19.8		17.6		55
60			1.79	24.0		21.6		19.2		60
65			1.65	26.0		23.4		20.8		65
70			1.54	28.0		25.2		22.4		70
75			1.43	30.0		27.0		24.0		75
80			1.34	32.0		28.8		25.6		80
90			1.19	36.0		32.4		28.8		90
100			1.08	40.0		36.0		32.0		100
125	0.86	50.0	45.0	40.0	125					
YL20x20	20	12	6.88	8.0	55	7.2	50	6.4	44	20
25			5.50	10.0		9.0		8.0		25
30			4.58	12.0		10.8		9.6		30
35			3.93	14.0		12.6		11.2		35
40			3.44	16.0		14.4		12.8		40
45			3.06	18.0		16.2		14.4		45
50			2.75	20.0		18.0		16.0		50
55			2.50	22.0		19.8		17.6		55
60			2.29	24.0		21.6		19.2		60
65			2.12	26.0		23.4		20.8		65
70			1.96	28.0		25.2		22.4		70
75			1.83	30.0		27.0		24.0		75
80			1.72	32.0		28.8		25.6		80
90			1.53	36.0		32.4		28.8		90
100			1.38	40.0		36.0		32.0		100
125	1.10	50.0	45.0	40.0	125					
150	0.92	60.0	54.0	48.0	150					

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YL22x25	22	12	8.00	10.0	80	9.0	72	8.0	64	25
30			6.67	12.0		10.8		9.6		30
35			5.71	14.0		12.6		11.2		35
40			5.00	16.0		14.4		12.8		40
45			4.44	18.0		16.2		14.4		45
50			4.00	20.0		18.0		16.0		50
55			3.64	22.0		19.8		17.6		55
60			3.33	24.0		21.6		19.2		60
65			3.08	26.0		23.4		20.8		65
70			2.86	28.0		25.2		22.4		70
75			2.67	30.0		27.0		24.0		75
80			2.50	32.0		28.8		25.6		80
90			2.22	36.0		32.4		28.8		90
100			2.00	40.0		36.0		32.0		100
125			1.60	50.0		45.0		40.0		125
150	1.33	60.0	54.0	48.0	150					
YL25X25	25	13	9.90	10.0	99	9.0	89	8.0	79	25
30			8.25	12.0		10.8		9.6		30
35			7.07	14.0		12.6		11.2		35
40			6.19	16.0		14.4		12.8		40
45			5.50	18.0		16.2		14.4		45
50			4.95	20.0		18.0		16.0		50
55			4.50	22.0		19.8		17.6		55
60			4.13	24.0		21.6		19.2		60
65			3.81	26.0		23.4		20.8		65
70			3.54	28.0		25.2		22.4		70
75			3.30	30.0		27.0		24.0		75
80			3.09	32.0		28.8		25.6		80
90			2.75	36.0		32.4		28.8		90
100			2.48	40.0		36.0		32.0		100
125			1.98	50.0		45.0		40.0		125
150	1.65	60.0	54.0	48.0	150					
175	1.41	70.0	63.0	56.0	175					
200	1.24	80.0	72.0	64.0	200					
YL30x25	30	18	14.60	10.0	146	9.0	131	8.0	116	25
30			12.17	12.0		10.8		9.6		30
35			10.43	14.0		12.6		11.2		35
40			9.13	16.0		14.4		12.8		40
45			8.11	18.0		16.2		14.4		45
50			7.30	20.0		18.0		16.0		50
55			6.64	22.0		19.8		17.6		55
60			6.08	24.0		21.6		19.2		60
65			5.62	26.0		23.4		20.8		65
70			5.21	28.0		25.2		22.4		70
75			4.87	30.0		27.0		24.0		75
80			4.56	32.0		28.8		25.6		80
90			4.06	36.0		32.4		28.8		90
100			3.65	40.0		36.0		32.0		100
125			2.92	50.0		45.0		40.0		125
150	2.43	60.0	54.0	48.0	150					
175	2.09	70.0	63.0	56.0	175					
200	1.83	80.0	72.0	64.0	200					

訂購方法：型號（顏色）-外徑 x 長度=數量

訂購示範：YL25x50=50pcs

交貨日期：現貨供應。

稱呼 Model	外徑 Outer Dia. (mm)	內徑 Inner Dia. (mm)	定數 Spring Const. (kgf/mm)	30 万 0.3million		50 万 0.5million		100 万 1million		自由長 Free Length (mm)
				壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	壓縮量 Deflection (mm)	荷重 Load kgf	
YL35x40	35	21	10.94	16.0	175	14.4	157	12.8	140	40
45			9.72	18.0		16.2		14.4		45
50			8.75	20.0		18.0		16.0		50
55			7.95	22.0		19.8		17.6		55
60			7.29	24.0		21.6		19.2		60
65			6.73	26.0		23.4		20.8		65
70			6.25	28.0		25.2		22.4		70
75			5.83	30.0		27.0		24.0		75
80			5.47	32.0		28.8		25.6		80
90			4.86	36.0		32.4		28.8		90
100			4.38	40.0		36.0		32.0		100
125			3.50	50.0		45.0		40.0		125
150			2.92	60.0		54.0		48.0		150
175			2.50	70.0		63.0		56.0		175
200			2.19	80.0		72.0		64.0		200
YL40x40			40	26		13.13		16.0		210
45	11.67	18.0			16.2	14.4	45			
50	10.50	20.0			18.0	16.0	50			
55	9.55	22.0			19.8	17.6	55			
60	8.75	24.0			21.6	19.2	60			
65	8.08	26.0			23.4	20.8	65			
70	7.50	28.0			25.2	22.4	70			
75	7.00	30.0			27.0	24.0	75			
80	6.56	32.0			28.8	25.6	80			
90	5.83	36.0			32.4	28.8	90			
100	5.25	40.0			36.0	32.0	100			
125	4.20	50.0			45.0	40.0	125			
150	3.50	60.0			54.0	48.0	150			
175	3.00	70.0			63.0	56.0	175			
200	2.63	80.0			72.0	64.0	200			
225	2.33	90.0			81.0	72.0	225			
250	2.10	100.0	90.0	80.0	250					
275	1.90	110.0	99.0	88.0	275					
300	1.75	120.0	108.0	96.0	300					
YL50x50	50	32	16.50	20.0	330	18.0	297	16.0	264	50
55			15.00	22.0		19.8		17.6		55
60			13.75	24.0		21.6		19.2		60
65			12.69	26.0		23.4		20.8		65
70			11.79	28.0		25.2		22.4		70
75			11.00	30.0		27.0		24.0		75
80			10.31	32.0		28.8		25.6		80
90			9.17	36.0		32.4		28.8		90
100			8.25	40.0		36.0		32.0		100
125			6.60	50.0		45.0		40.0		125
150			5.50	60.0		54.0		48.0		150
175			4.71	70.0		63.0		56.0		175
200			4.13	80.0		72.0		64.0		200
250	3.30	100.0	90.0	80.0	250					
300	2.75	120.0	108.0	96.0	300					
YL60X60	60	33	23.96	24.0	575	21.6	517	19.2	460	60
70			20.54	28.0		25.2		22.4		70
80			17.97	32.0		28.8		25.6		80
90			15.97	36.0		32.4		28.8		90
100			14.38	40.0		36.0		32.0		100
125			11.50	50.0		45.0		40.0		125
150			9.58	60.0		54.0		48.0		150
175			8.21	70.0		63.0		56.0		175
200			7.19	80.0		72.0		64.0		200
250			5.75	100.0		90.0		80.0		250
300	4.79	120.0	108.0	96.0	300					